

Burglar Alarm

PSTN Control System

FC-7668 PRO

- 8 tamper-checking wired zone,32 wireless zone.
- 8 programmable access wireless remote.
- 8 programmable access keypad, 32 wireless appliance switch,8 wireless siren.
- Can extend GPRS wireless communication module, support GPRS data transmission.
- Can extend programmable Relay module,serial module.
- Can set 8 private telephone numbers.
- Remote voice prompt operation.



FC-7668 is a intelligent alarm control system which integrated with burglar proof, fireproof, gas leak proof. it is compatible with wired and wireless alarm mode. it use advanced coding techniques of BUS zone and multi-bit random code hopping techniques in security and reliability. to avoid false alarm and interference effectively. adopt SMS, 2G/4G, high-speed Contact ID alarm transmission mode. this system is wurdely used in residence community, villa, shops, offices.

Specification

| General | |
|---------------------------------|---|
| System NetworkT | TCP/IP+2G/4G Dual NetworkT |
| Alarm Zones | 32 Wireless+8 Wired + 56 RS485 + 32 Power Bus |
| Dimensions | 290x240x87 mm (WXHxD) |
| Housing Material | ABS Fire-resistant Box |
| Wireless Frequency | 433MHz/868MHz |
| Installation Location | Indoor Use For Wall Mounted |
| Menu Voice Guidance | Customized |
| DHCP Function | Support |
| Duress Password | Yes |
| Entry & Exit Delay | Yes |
| Number of Users | 32 Users + 1 Admin +1 Main |
| Number of voice phone No. | 16 |
| Number of wireless remotes | 8 |
| Number of wired keypad | 16(Each keypad support extra 3 wired zones) |
| Number of wireless doorbell | 1 |
| Number of wireless Switch | 32Ch |
| Partitions And Areas | 8 |
| Event log | 512 |
| Wireless Siren | 4 for dual way siren, multiple for single way siren |
| PGM Outputst | 4 |
| Event log | 1000 |
| Backup Battery Type | 12V DC, 7ah lead acid battery |
| Max. run time on backup Battery | 16 h if connect 1 wired keypad |
| Max. receiving range (outdoors) | 100 m |
| Max. sending range (Outdoors) | 150 m |

| | |
|--------------------------|--|
| Power Supply Unit | 15V/3A |
| GSM Dialing Protocols | Ademco Contact ID |
| IP/GPRS CMS protocol | SIA-TCP, SIA-UDP, Meian CMS |
| CMS Platform Docking Way | Support 2 CMS Server Address Main Server +Backup Server (Meian Server/SIA-TCP,SIA-UDP) |
| Camera Supported | Support |
| WEBIE | Support |
| Packing | 4 Sets/Carton |
| Certifications | CE,FCC,ROHS |