

# Curtain PIR

Motion Detector Wired



**MD-442DMT**



**MD-448DMT**



**DDP-968**

## Specification

Overview		Overview		Overview	
Detection	Quad Infrared	Detect angle	200°	Detection	2group quad PIR + dual MW
Working voltage	9~15VDC	Detect distance	6m/25°C	Detection distance	3m@25°C
Working current	8mA~25mA	Transmit distancet	150m (open air)	Detection angle	20°
Alarm output	solid relay ,NC output	Current consumption	standy <25µA. when transmitting 10mA	MW frequency	10.525GHz
Tamper interface	N.C, 50mA/30VDC	Alarm output	wireless signal transmitting	Working voltage	9VDC~15VDC
Anti-white light	wireless signal transmitting	Anti-tamper output	wireless signal transmitting	Working current	100µA(standby) 35mA(alarm)
Transmitting frequency	>8000LUX	Transmitting frequency	433MHz	Installation	height : 1.8m~2.4m
Installation mode	wall-mounted or Ceiling	LED indication	Red LED on stands making alarm blue LED on and red led off stands get signal but wrong direction.	Working temperature	-10°C - +50°C
Installation height	Max.4.8m	Wall mount height	2.5-4m	Anti-white light	>15000LUX
Dimension	86×86×50mm	Woking temperature	-10°C-50°C (14°F-122°F)	Anti-EMI	>30V/m (30MHz~1GHz)
				Emitting frequency	433MHz/868MHz
				Emitting power	≤10dB
				Dimension	230mm×66mm×36mm