

Home Alarm

Intrusion Security System

HVA-VGT

- Home Monitor HD Pro Camera (Support 8 PCS With Meian Cameras)
- With TCP/IP RJ45 Ethernet Port, Stable And More reliable.
- With Wireless PIR Motion Detector, Door Magnetic Sensor, Remote Controller.
- All the Wireless Device With Lithium Battery.
- No Need to Change Battery frequently. It can keep using for 3-5 Years.
- With pet immunity, door open/closed notification, Low battery indication,
- Alarm video linkage functions.
- Intercom for talking, timing arm/disarm.



4G Smart home alarm, LAN IP, GPRS network, SIA + Wi-Fi camera with iOS/Android app push notifications. 2.8 inch TFT Color Display & Glass Touch Panel, TCP/IP 2G/4G With IP camera Home Security Alarm System

Specification

General

RF Radio Frequency	ASK 433/868mhz
Dimensions	280x205x74mm (wxhxd)
Housing Material	ABS Cover+Tempered Glass
LCD Size	2.8" LCD display
System Network	TCP/IP+GSM/GPRS (4G)
DHCP Function	Support
Admin Password	1
User Password	16
Voice Phone No.	4
CMS Phone No.	2
Number Wired Zones	8
Remote and Keypads	8
Number of RFID tags (125KHz)	16
Number of wireless Zones	32
Wireless doorbell	1
Wireless Switch	16Ch
Programmable Wired Output	1
Event log	512
Wireless Siren	Support
Anti-tamper Alarm	Support
Programmable Wired Output	1
GSM Antenna:	External
Integrated Siren	Yes (85dB @ 1m)
Backup Battery	7.4V/1A
Max. run time on backup Battery	6 h
Max. receiving range (outdoors)	100 m
Max. sending range (Outdoors)	150m

Power Supply Unit	12V/1.5A
GSM Band Frequency	850/900/1800/1900mhz
GSM Dialing Protocols	Ademco Contact ID
Firmware Upgrade Way	Web GUI/SD Slot
IP/GPRS CMS protocol	SIA-TCP, SIA-UDP, CMS Client
Mobile Client APP	Support
GSM Dialing Protocols	Ademco Contact ID
Firmware Upgrade Way	Web GUI/SD Slot
IP/GPRS CMS protocol	SIA-TCP, SIA-UDP, CMS Client
Mobile Client APP	Support
Camera Supported	Support
Packing	10 Sets/17.5kg/Carton
Certifications	CE,FCC,ROHS