


Ingenic

IP Module

T881



8MP H.265+



Human detection IP module, resolution 8MP (3840*2160 @20fps), 5MP(2592*1904@25fps), 4MP (2560*1440 @25fps), 3MP (2304*1296 @25fps), 2MP (1920*1080 @25fps), support two-way intercom, human alert voice broadcast, H.265+ / H.265 / H.264 compression format, D-WDR, 3D DNR, support 4 kinds of IR light boards: IR light, sensor trigger, warm light, dual lights, support to connect IO board, TF card (512G), alarm, RS485, wifi, reset, support 4G module.

Highlight

- Resolution 8MP (3840*2160@20fps), 5MP (2592*1904@25fps), 4MP (2560*1440@25fps), 3MP (2304*1296@25fps), 2MP (1920*1080@25fps)
- Built-in humanoid detection algorithm
- Detection frame 10fps, detect 10 people at the same time
- Low consumption, low code stream, low delay
- H.265+ compression format, save bandwidth and storage space
- Support Smart IR to avoid Infrared over-exposure at night
- Support ICR auto switch, achieve best result for D&N video
- Support PoE (option)
- With SD/TF card slot for local storage
- Support smart auto startup SD/TF card record offline
- Support alarm, reset, wifi, RS485 and 4G module
- Support 3D DNR and digital WDR, defog
- Support auto-electronic shuttle to suit different surveillance environment
- Support two-way audio intercom
- Support HTTPS encrypted transmission
- Support Onvif, email, NTP service
- Change the password during initial use to ensure the security of the password

Specification

Camera	
DSP	T31N
Sensor	Color 1/2.9" Low Illumination CMOS Sensor
Lens	Support fixed lens and manual varifocal lens
D&N	ICR Switch, Auto/Color/B&W/CDS Trigger
D-WDR	D-WDR (off/low/middle/high)
Light board control	IR light, warm light, dual lights, auto/manual/off, support 0-100 brightness adjustable
3D DNR	Off/Low/Middle/High/Higher
Defog	Off/Low/Middle/High
Mirror	Off/ Horizontal Mirror/Vertical Mirror/180-degree flip
Image Setting	Brightness, Contrast, Sharpness, Saturation, Chroma

Audio & Video Encoding	
Video Encode Standard	H.265+/H.265/H.264
Encoding Feature	Main stream: 8MP(3840*2160)20fps, 5MP(2592*1904) 4MP(2560*1440) 3MP(2304*1296) 2MP(1920*1080) 25fps Sub-stream: D1 (720*576), VGA (640*360)
Max resolution	3MP (2304*1296)
Video Code Rate	Fixed code rate, variable code rate (Main stream: 160Kbps-4000kbps)
Video Type	Composited stream/video stream
Audio Standard	G.711u / 64Kbps

Human Detection

Detection Quantity	10 people human
Humanoid Size	Human Pixel $\geq 40 \times 40$
Detection Ratio	$\geq 99\%$ (meet above requirement)
Capture Corresponding Speed	$\leq 1s$
Max Detection Frame	15fps/s
Fault Detection Ratio	$\leq 2\%$
Detection Part	People with any posture including half body, head, hand, shoulder
Track People	Support
Detection Mode	Support static and dynamic human detection
Detection method	Image detection during day time or night time with lights or IR LEDs
Detection Area	Appointed area, default full-screen
Upload Method	Upload it under private protocol
Trigger Method	Video trigger

General

Power Supply	DC12V /PoE (option)
Size	38*38mm
Working Temperature	-10°C ~ 50°C
Working Humidity	0%~90%

Network Function

Protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, RTSP, DDNS, NTP, PPPOE, UPNP, SMTP
Connection Protocol	ONVIF, GB28181(Optional)
Security Mode	Authorized user name and password, HTTPS encryption, AES connecting encryption, RTSP verification
Motion Detection	Set detection area, can set multi-level sensitivity
Shield Alarm	Support 1 area
Privacy Mask	Support 4 areas
Schedule Linkage	Snapshot, TF card recording, email, alarm output, voice broadcast, alarm light
Device abnormal Inspection	Support network broken alarm, IP conflict alarm, illegal visiting alarm
Character Overlay (OSD)	Title, time and date overlay, multi-line, and color of characters optional

Port

Network Port	Rj45 10M/100M network self-adaptation
Audio	MIC Input/ Output
Rs485	Support
Alarm	Support
Reset	Support
SD/TF card slot	Support
USB port	Support USB WiFi/4G module to connect

Interface Definition

